



Front hot-air fireplace.

Opening to side.
Door with frame.

Door width: 70 cm
Door height: 45 cm
Efficiency: 85 %
Adjustable output: 7 - 12 kW
With grate and ashtray.

Extras:
Hot-air exchanger.
Cladding in colours (grey, anthracite).

| | |
|--|---------------------------|
| Min. chimney diameter | 180 mm |
| Min. operating chimney draught | 12 Pa |
| Diameter of external air nozzle | 120 mm |
| Volume of air needed for burning | 26 m ³ /h |
| Distance from wall | 7 cm |
| Size of grilles (lower/upper) | 1450/1550 cm ² |
| Efficiency | 85 % |
| Adjustable output | 7 - 12 kW |
| Nominal output | 9,5 kW |
| Fuel | Wood, wood briquettes |
| Log size | 33 cm |
| Fuel consumption | 2,6 kg/h |
| Heated space | ~105 - 333 m ³ |
| Weight | 192 kg |
| Content of water in wood | < 20 % |
| CO content at 13% O ₂ | 0,09 % |
| Average flue gas temperature behind smoke socket (at nominal output) | 209 °C |
| Flue gas mass flow | 7,4 g/s |
| Min. heat exchanging surface | x |

| | | | |
|-----------------------|----|-------------------|----|
| EN 13229:2002/A2:2005 | ok | BlmSchV. 1. Stufe | ok |
| Bauart A2 | ok | BlmSchV. 2. Stufe | ok |
| Bauart A1 | ok | Art. 15a B-VG | ok |
| DINplus | ok | | |

