



Front hot-air fireplace.

Vertical opening, possibility of front opening for glass cleaning.
Frameless door - design glass.

Door width: 90 cm
Door height: 45 cm
Efficiency: 82 %
Adjustable output: 10 - 17 kW

With grate and ashtray.

Extras:
Hot-air exchanger.
Cladding in colours (grey, anthracite).

Min. chimney diameter	200 mm
Min. operating chimney draught	12 Pa
Diameter of external air nozzle	150 mm
Volume of air needed for burning	45 m ³ /h
Distance from wall	7 cm
Size of grilles (lower/upper)	2300/2500 cm ²
Efficiency	82 %
Adjustable output	10 - 17 kW
Nominal output	15 kW
Fuel	Wood, wood briquettes
Log size	33 cm
Fuel consumption	4,5 kg/h
Heated space	~195 - 420 m ³
Weight	330 kg
Content of water in wood	< 20 %
CO content at 13% O ₂	0,09 %
Average flue gas temperature behind smoke socket (at nominal output)	262 °C
Flue gas mass flow	10,9 g/s
Min. heat exchanging surface	x

EN 13229:2002/A2:2005	ok	BlmSchV. 1. Stufe	ok
Bauart A2	ok	BlmSchV. 2. Stufe	ok
Bauart A1	ok	Art. 15a B-VG	ok
DINplus	ok		

