



Front hot-air fireplace.

Vertical opening, possibility of front opening for glass cleaning.
Frameless door - design glass.

Door width: 70 cm
Door height: 45 cm
Efficiency: 85 %
Adjustable output: 7 - 12 kW

With grate and ashtray.

Extras:

Hot-air exchanger.
Cladding in colours (grey, anthracite).

Min. chimney diameter	180 mm
Min. operating chimney draught	12 Pa
Diameter of external air nozzle	120 mm
Volume of air needed for burning	26 m ³ /h
Distance from wall	7 cm
Size of grilles (lower/upper)	1450/1550 cm ²
Efficiency	85 %
Adjustable output	7-12 kW
Nominal output	9,5 kW
Fuel	Wood, wood briquettes
Log size	33 cm
Fuel consumption	2,6 kg/h
Heated space	~105 - 333 m ³
Weight	255 kg
Content of water in wood	< 20 %
CO content at 13% O ₂	0,09 %
Average flue gas temperature behind smoke socket (at nominal output)	209 °C
Flue gas mass flow	7,4 g/s
Min. heat exchanging surface	x

EN 13229:2002/A2:2005	ok	BlmSchV. 1. Stufe	ok
Bauart A2	ok	BlmSchV. 2. Stufe	ok
Bauart A1	ok	Art. 15a B-VG	ok
DINplus	ok		

